

LEVANTE

VEGAN LEATHER

Levanté Vinyl features a PreFixx protective finish, enhancing its unique combination of leather-like texture, suppleness, and long-lasting construction. Its supple feel and robust design makes it an excellent choice for demanding environments like hospitality and healthcare, offering both style and resilience. Additionally, it is flexible and easy to handle.



Fade Resistant



Stain Resistant



Bacterial Resistant



Urine & Oil Resistant



5 year indoor warranty



Exceptional durability



Waterproof



Bleach & Isopropyl Cleanable



Easy Maintenance



Versatile Applications



MAS Certified Green®

MAS Certified Green® Certificates of Compliance - What it means for you:

- Increased product options for customers who require certified low VOC emitting materials
- Reduced indoor air pollution, contributing to healthier living and working environments
- Independent validation of our suppliers commitment to safety and quality
- Demonstrates our suppliers proactive commitment to obtaining industry certifications relevant to its customer base



PreFixx Finish

PreFixx® protective finish is engineered so that upholstery can be cleaned again and again without showing signs of wear. With easy cleanability, and proven stain and abrasion resistance, PreFixx can reduce maintenance costs and extend the upholstered product's useful life.

PreFixx is bleach and isopropyl alcohol cleanable, allowing for hassle-free disinfection using a wide range of hospital-grade disinfectants.







Levante





Levate



Properties	
Face Composition	PVC
Backing Composition	Non-Woven Polyester
Attributes	Prefixx Coating
Product Type	Heavy Commercial
Roll Size (approx)	45.7m & 30m
Styles	Flat Emboss
Stain Repellent	Yes
Bleach & Isopropyl Cleanable	Yes
Usage	Healthcare, Marine, Aged care, Hospitality, Commercial, General Upholstery
Warranty	5 Years in accordance with our product type and care instructions
Test Results	
Weight (ASTM D 751 79)	22 oz/lin yd
Width (CFFA-700a)	137 cm (54in)
Thickness	1.00mm
Flamibility	Cal Tech 117 Section 3
	UFAC Fabric, Class 1
	NFPA 260 Class 1
Protective Finish	Prefixx Coating
Use	Indoor
Trap Tear Strength #, min (CFFA-16c)	38 Warp, 38 Fill
Tensile Strength #, min (CFFA-17)	86 Warp, 88 Fill
Adhesion #/in., min (CFFA-3)	4 Warp, 4 Fill
Tack Strength #,min (CFFA-14)	56 Warp, 53 Fill
Wyzenbeek Abrasion (CFFA-1a)	1,300,000 Cotton Duck (double rubs)
W-Flex - 25,000 cycles (CFFA-10)	Pass
QUV-B 500 Hours	Pass
Crocking Resistance - 20 cycles no stain (CFFA-7)	Pass
Biocompatibility Certified ISO 10993	Pass
Fungal Resistance (ASTM-G-21)	Pass
Bacterial Resistance (AATCC 147)	Pass
Bacterial Resistance (AATCC 100)	Pass