



Melange is a **Boltaflex Ethos** vinyl performance fabric from Textile House featuring our industry-leading **PreFixx** protective coating. Formulated without phthalates, fire retardants (FR), and antimicrobial (MR) additives, **Boltaflex Ethos** vinyl performance fabric support the growing trend towards eco-friendly solutions in contract design. *Melange* features a beautifully printed textile-like design in a palette of on-trend colors perfect for office, hospitality, and healthcare settings. **Boltaflex Ethos** vinyl performance fabric are formulated with only those ingredients needed to provide durability, performance, and comfort.

Industries & Markets

- Corporate Office
- Food Service
- Healthcare
- Hospitality & Entertainment

End-Use Applications

- Office Furniture
- Contract Seating
- Dining Seating
- Medical Furnishings
- Guest room furnishings
- Lobby furnishings & millwork
- Theater Seating

Physical Specifications

Weight (CFFA-700d)	28 oz/lin yd [18.7 oz/yd ²]
Weight, Metric (CFFA-700d)	849 g/lin m [619 g/m ²]
Width (CFFA-700a)	54 in. [137 cm]
Face Composition	PVC
Backing Description	Polyester Terry Loop Knit
Roll Size	40 lin yd [37 lin m]
Emboss Level	Light
Shipping Weight/ Roll	68 lb [31 kg]

Flame, Smoke & Toxicity

Meets or exceeds the following:	<ul style="list-style-type: none">• BIFMA - Class A• Cal Tech 117-2013 Sec 1• NFPA 260, Class 1• UFAC Fabric, Class 1• AB 2998• IMO Part 8 Upholstered Furniture 3.1 Smoldering Cigarette
---------------------------------	--

Performance Features

Protective Finish	PreFixx
Use	Indoor
Repeat	18
Adhesion #/in., min (CFFA-3)	4 Warp, 4 Fill
Tensile Strength #, min (CFFA-17)	85 Warp, 75 Fill
Tack Strength #, min (CFFA-14)	35 Warp, 30 Fill
Trap Tear Strength #, min (CFFA-16c)	20 Warp, 27 Fill
Wyzenbeek Abrasion (CFFA-1a)	1,200,000 Cotton Duck (double rubs)
Blocking (CFFA-4 No. 1)	Pass
W-Flex - 25,000 cycles (CFFA-10)	Pass
Crocking Resistance - 20 cycles no stain (CFFA-7)	Pass
Cold Crack (CFFA-6a)	-20 °F [-29 °C]
Compatible with Disinfectants	Yes.
Bleach-Safe	Yes, 10% Bleach Solution
Resistance to Sulfide Stain (ASTM D1712)	Yes
Oil Resistance (CFFA-13)	Yes
Urine Resistance (AATCC-6)	Yes

Revision Date: 15-August-22

Note: Due to possible variances in your computer monitor, the colors and patterns displayed may vary slightly from the actual product. Customers should always obtain and compare actual samples before specifying.



Distributed by:
Textile House
100 John Street
Pukekohe
2120 New Zealand
P | 0800 644 445
F | 0800 65 99 00

All Textile House products and services are offered and sold subject to the Textile House standard terms and conditions apply.

Trademarks are property of Textile House unless otherwise noted.

©2022 Textile House